

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
22 August 2002 (22.08.2002)

PCT

(10) International Publication Number
WO 02/065753 A1

- (51) International Patent Classification⁷: **H04N 1/32**,
G06T 1/00, H04N 5/913, G11B 20/00
- (21) International Application Number: PCT/IB02/00414
- (22) International Filing Date: 11 February 2002 (11.02.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
01200523.7 13 February 2001 (13.02.2001) EP
- (71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (74) Agent: **SCHMITZ, Herman, J., R.**; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (*national*): CN, JP, KR, US.
- (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **KALKER, Antonius**,

(54) Title: METHOD AND ARRANGEMENT FOR DETECTING A WATERMARK IN AN INFORMATION SIGNAL



(57) Abstract: A pseudo-symmetric watermark is watermark pattern that is built up from a finite number of basic pattern by tiling. The well-known WaterCast pattern that is built up from one single pattern is a special case of this, and is referred to as a symmetric watermark pattern. It is well known that symmetric patterns allow an efficient detection method that consist of two phases, viz. first an accumulation phase, followed by a cyclic sliding correlation with the basic pattern over the accumulated data. The invention provides a detection method for pseudo-symmetric watermarks with a similar reduction in complexity as with symmetric watermarks, i.e. an accumulation phase followed by one or more cyclic sliding correlation steps (using the finite number of basic patterns). Let W_1, \dots, W_N be the set of basic patterns, all of size M . The suspect signal is folded (31) as if there was only a single basic pattern. The fold buffer will have the sum

pattern $W = W_1 + \dots + W_N$ (39) as a strong component. The presence of the watermark can then be detected by a cyclic sliding correlating with W .

WO 02/065753 A1

Method and arrangement for detecting a watermark in an information signal

FIELD OF THE INVENTION

The invention relates to a method and arrangement for detecting a watermark in an information signal.

5 BACKGROUND OF THE INVENTION

Various methods of embedding a watermark in an information (e.g. video, audio) signal, and corresponding methods of detecting said watermark, are known in the art.

International patent application WO99/12331 discloses a known embedding and detecting method. In this prior art method, different watermark patterns are embedded in
10 respective sections of an information signal (here: image blocks into which the image is divided). Such a watermark, which is built up from a finite number of basic pattern by tiling, is herein referred to as a pseudo-symmetric watermark.

OBJECT AND SUMMARY OF THE INVENTION

15 It is an object of the invention to provide a method and arrangement for detecting the watermark.

To this end, the method comprises the steps of accumulating said sections, and correlating the accumulated sections with the sum of the basic watermark patterns.

The invention is based on the insight that a known methodology of detecting
20 symmetric watermarks can also be applied to pseudo-symmetric watermarks. International patent application WO 99/45705 discloses a art method of embedding and detecting symmetric watermarks. In this method, a watermark is embedded in a video signal by repeating a single small-sized basic watermark pattern over the extent of the video image. This "tiling" operation allows the watermark detection process to search the watermark over a
25 relatively small space and improves the reliability of detection. A data payload is encoded into the basic watermark tile. As disclosed in WO 99/45705, the watermark is detected by accumulating or "folding" the sections of the image in a buffer (128x128 pixels in a practical embodiment) and correlating the buffer contents with the single 128x128 basic watermark pattern. Applying Symmetrical Phase Only Matched Filtering (SPOMF) in the detector

renders the relative position of the reference watermark with respect to the image irrelevant. The known detector is thus invariant with respect to translation and cropping, two processes that the image may have undergone prior to watermark detection. SPOMF also makes it possible to easily encode a multi bit payload in the basic watermark pattern.

5 The inventors have found that the detection method known from WO 99/45705 can also effectively and reliably be applied to pseudo-symmetric watermarks if the following conditions are fulfilled: (1) each of the multiple patterns occurs with approximately equal probability, (2) the patterns are pairwise orthogonal or at least have little correlation, and (3) the patterns are all of equal size.

10 A particular advantage of the invention is that complicated circuits of different watermark detectors can be shared, if multimedia content is watermarked by pseudo-symmetric as well as symmetric watermarks. It is currently envisaged to merge two such different watermark embedding methods (although not necessarily the two methods mentioned above).

15 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows schematically an image with an embedded pseudo-symmetric watermark in the form of multiple basic watermark patterns $W_1..W_N$.

20 Fig. 2 shows a schematically an embodiment of a watermark detector in accordance with the invention.

Fig. 3 shows a diagram to illustrate an operation carried out by the watermark detector which is shown in Fig. 2.

DESCRIPTION OF EMBODIMENTS

25 Fig. 1 shows schematically an image with an embedded pseudo-symmetric watermark in the form of multiple basic watermark patterns $W_1..W_N$.

Fig. 2 shows a practical embodiment of a watermark detector in accordance with the invention. The detector receives possibly watermarked images Q . The image (or a number of accumulated video frames) is partitioned into blocks having the size $M_1 \times M_2$ of the basic watermark pattern (here 128×128). The blocks are then stacked in a buffer q of size $M_1 \times M_2$ as illustrated in Fig. 3. These operations are carried out by a folding and buffer circuit
30
31.

By folding the suspect signal as if there was only a single basic pattern, the fold buffer will have the sum pattern $W=W_1+..+W_N$ as a strong component. The presence of

the watermark can then be detected by a cyclic sliding correlating the buffer contents with W. The reliability thereof down with a factor $\text{Sqrt}[N]$ with respect to optimal correlation (i.e. synchronized correlation with the full signal watermark).

In order to correlate the buffer contents with W, the detector comprises an adding stage 39 in which the basic watermark patterns W_1 - W_N are sample wise added.

The operation of the detector further corresponds with the disclosure of WO 99/45705 and will here briefly be repeated. Computing the correlation of a suspect information signal q with a watermark pattern w comprises computing the inner product $d = \langle q, w \rangle$ of the information signal values and the corresponding values of the watermark pattern. For the two-dimensional $M_1 \times M_2$ image block $q = \{q_{ij}\}$ and watermark pattern $W = \{w_{ij}\}$, the inner product can be written in mathematical notation as:

$$d = \frac{1}{M_1 M_2} \sum_{i=1}^{M_1} \sum_{j=1}^{M_2} q_{ij} w_{ij} .$$

Because the suspect image Q may have undergone manipulations such as translation or cropping prior to the watermark detection, the detector does not know the spatial location of the watermark pattern W with respect to the boundaries of image block q. A multiple of correlations d_k must therefore be calculated for all possible shift vectors k (k_x pixels horizontally and k_y pixels vertically):

$$d_k = \frac{1}{M_1 M_2} \sum_{i=1}^{M_1} \sum_{j=1}^{M_2} q_{ij} w_{i+k_x, j+k_y}$$

Said correlation values d_k can be simultaneously computed using the (Fast) Fourier Transform. Both the contents of buffer q and the basic watermark pattern W are subjected to a Fast Fourier Transform (FFT) in transform circuits 32 and 33, respectively. These operations yield:

$$\hat{q} = \text{FFT}(q) \text{ and}$$

$$\hat{w} = \text{FFT}(w),$$

where \hat{q} and \hat{w} are sets of complex numbers.

Computing the correlation is similar to computing the convolution of q and the conjugate of W. In the transform domain, this corresponds to:

$$\hat{d} = \hat{q} \otimes \text{conj}(\hat{w})$$

where the symbol \otimes denotes point wise multiplication and $\text{conj}()$ denotes inverting the sign of the imaginary part of the argument. In Fig. 3, the conjugation of \hat{w} is carried out by a conjugation circuit 34, and the point wise multiplication is carried out by a multiplier 35.

The set of correlation values $d=\{d_k\}$ is now obtained by inverse Fourier transforming the result of said multiplication:

$$d = \text{IFFT}(\hat{d})$$

which is carried out by an inverse FFT circuit 36. The correlation values d_k are subsequently compared with a given threshold in a threshold circuit 37. The image is detected to be watermarked if one of the correlation values has a significant peak, i.e. larger than the threshold.

If it is necessary to detect whether the individual patterns W_1-W_N are embedded, the same circuit can be used. The pattern to be checked (W_1, W_2 , etc.) is then applied only to the arrangement which is shown in Fig. 2.

In a further embodiment of the method according to the invention, the size- M fold buffer is used to retrieve the position of the 128×128 tiling grid. Using the synchronized tiling grid, the the partial correlations $C_{ij} = \langle Y_i, W_j \rangle$ are computed, where i is the i th suspect signal tile, W_j is as before, and $\langle \rangle$ denotes the inner product. This reduces the translation search to steps over the grid, using only the partial correlation values C_{ij} . If there is additional structure in the full watermark, e.g. in case of a higher level symmetry in terms of the tiles W_i , then very efficient detection is possible.

The invention can be summarized as follows. A pseudo-symmetric watermark is watermark pattern that is built up from a finite number of basic pattern by tiling. The well-known WaterCast pattern that is built up from one single pattern is a special case of this, and is referred to as a symmetric watermark pattern. It is well known that symmetric patterns allow an efficient detection method that consist of two phases, viz. first an accumulation phase, followed by a cyclic sliding correlation with the basic pattern over the accumulated data. The invention provides a detection method for pseudo-symmetric watermarks with a similar reduction in complexity as with symmetric watermarks, i.e. an accumulation phase followed by one or more cyclic sliding correlation steps (using the finite number of basic patterns). Let W_1, \dots, W_N be the set of basic patterns, all of size M . The suspect signal is folded (31) as if there was only a single basic pattern. The fold buffer will have the sum pattern $W = W_1 + \dots + W_N$ (39) as a strong component. The presence of the watermark can then be detected by a cyclic sliding correlating with W .

CLAIMS:

1. A method of detecting a watermark in an information signal, the watermark being embedded by tiling a finite number of different basic watermark patterns in respective sections of the information signal, comprising the steps of accumulating said sections, and correlating the accumulated sections with the sum of the basic watermark patterns.
5
2. The method as claimed in claim 1, wherein the correlation value is used to determine the presence and/or payload of the watermark.
3. The method as claimed in claim 1, wherein the correlation value is used to
10 determine the position of the tiling grid.
4. The method as claimed in claim 1, further comprising the step of correlating individual sections with individual basic patterns.
- 15 5. The method as claimed in claim 3 and 4, wherein the tiling grid is used to locate the individual sections.
6. An arrangement for detecting a watermark in an information signal in accordance with the method as claimed in any one of claims 1-5.

1/1




Fig.1




Fig.2




Fig.3

INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/IB 02/00414

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04N1/32 G06T1/00 H04N5/913 G11B20/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04N G06T G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 99 45705 A (KALKER ANTONIUS A C M ;KONINKL PHILIPS ELECTRONICS NV (NL); PHILIP) 10 September 1999 (1999-09-10) the whole document	1-6
Y	& WO 99 45704 A (...) 10 September 1999 (1999-09-10) abstract	1-6
Y	WO 00 04722 A (KONINKL PHILIPS ELECTRONICS NV) 27 January 2000 (2000-01-27) abstract	1-6
Y	EP 0 967 803 A (NIPPON ELECTRIC CO) 29 December 1999 (1999-12-29) the whole document	1-6
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

° Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

15 April 2002

Date of mailing of the international search report

06/05/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Luckett, P

INTERNATIONAL SEARCH REPORT

Int al Application No
PCT/IB 02/00414

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	KALKER T ET AL: "A VIDEO WATERMARKING SYSTEM FOR BROADCAST MONITORING" PROCEEDINGS OF THE SPIE, SPIE, BELLINGHAM, VA, US, vol. 3657, 25 January 1999 (1999-01-25), pages 103-112, XP000949142 the whole document ---	1-6
A	MAES M ET AL: "EXPLOITING SHIFT INVARIANCE TO OBTAIN A HIGH PAYLOAD IN DIGITAL IMAGE WATERMARKING" PROCEEDINGS OF THE INTERNATIONAL CONFERENCE ON MULTIMEDIA COMPUTING AND SYSTEMS, LOS ALAMITOS, CA, US, vol. 1, June 1999 (1999-06), pages 7-12, XP000939264 the whole document -----	1-6

INTERNATIONAL SEARCH REPORT

Int: 1al Application No

PCT/IB 02/00414

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9945705	A	10-09-1999	AU 2437499 A	20-09-1999
			CN 1266586 T	13-09-2000
			CN 1266587 T	13-09-2000
			CN 1269098 T	04-10-2000
			CN 1269099 T	04-10-2000
			EP 0981900 A2	01-03-2000
			EP 0981901 A2	01-03-2000
			EP 0981902 A2	01-03-2000
			EP 0981903 A2	01-03-2000
			WO 9945704 A2	10-09-1999
			WO 9945705 A2	10-09-1999
			WO 9945706 A2	10-09-1999
			WO 9945707 A2	10-09-1999
			JP 2001525151 T	04-12-2001
			JP 2002503431 T	29-01-2002
			JP 2001525152 T	04-12-2001
			JP 2001525153 T	04-12-2001
			PL 336841 A1	17-07-2000
			PL 336845 A1	17-07-2000
WO 0004722	A	27-01-2000	CN 1273747 T	15-11-2000
			WO 0004722 A1	27-01-2000
			EP 1038402 A1	27-09-2000
			TW 395133 B	21-06-2000
EP 0967803	A	29-12-1999	US 6154571 A	28-11-2000
			CN 1238439 A	15-12-1999
			EP 0967803 A2	29-12-1999
			JP 2000138818 A	16-05-2000
			US 6278792 B1	21-08-2001